


K4-21.0KW

Standard Features

- Kubota Diesel Engine
- Single bearing direct coupled brushless generator
- +/- 1% Solid-state voltage regulation
- Low 1,800 RPM operating speed
- Safety shutdown system for high coolant temperature or low lube oil pressure
- Tinned wiring
- Freshwater double pass heat exchanger
- Water-cooled exhaust manifold with removable intergral Cupro-Nickel heat exchanger core
- Zinc anode in heat exchanger
- Stainless Steel exhaust elbow cast
- Gear-driven raw water pump
- 4-Point isolation mounts S/S
- Molded blue silicone water hoses with Stainless Steel AWAB clamps
- Air intake Cleaner / Silencer
- Spin-on lube filter
- Secondary 5 Micron fuel filter
- Self-bleed fuel system
- USCG approved fuel lines
- Electric fuel transfer pump
- Forged brass oil drain valve with safety lock
- Awl-Craft 2000 urethane finish
- Circuit breaker - main line
- Belt guard
- 5-Year Limited Warranty



Specifications

Kubota Model	V2403-M-E4BG
Cylinders	4
Cu. In. Displacement	148.5
Bore x Stroke	3.43 x 3.64 (in.)
Dims (LxWxH)	39.5 x 21 x 26 (in.)
Enclosure Dims (LxWxH)	43 x 24 x 28 (in.)
Weight (lbs.)	776
Output (volts)	120/240
Output (amps)	175/87.5
Output (watts)	21,000
Exhaust Dia.	2 in.
Raw water Dia.	1 in.
Fuel Line Dia.	5/16 in.
Return Line Dia.	3/16 in.

Specifications are subject to change without notice

Optional Equipment

- Start / Stop - 20 ft. harness
- Custom remote engine / generator instrument panels
- DC Gauge panel - 20 ft. harness
- Stainless Steel drip pan
- Three phase generator output
- 24 Volt starting system
- 50 cycle output
- Dedicated motor starting generator windings
- Sound insulation blanket
- Powder coated aluminum enclosure
- Remote oil filter kits
- Custom chrome packages
- Spare parts kit



2880 Hammondville Road • Pompano Beach, FL 33069
Ph: 954-979-5899 • Fax: 954-979-4349
info@phasormarine.com • www.phasormarine.com

rev020316